



SPECS

RAMME	
STØRRELSE	S, M, L, XL
FARGE	Knight Shield / Carbon
RAMME	Advanced-Grade Composite, 12x148mm thru-axle
GAFFEL	RockShox SID SL, 100mm, 44mm offset, Boost 15x110mm Maxle Stealth, tapered steerer, remote lockout
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact SL XC Flat, 780x31.8mm
GRIPS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
STYRSTEM	Giant Contact S:60mm, M:70mm, L:80mm, XL:90mm
SETEPINNE	composite, 30.9x400mm
SADEL	Fi'zi:k Antares R7 with S-Alloy rails
PEDALER	N/A
DRIVVERK	
GIRHENDLER	SRAM NX Eagle, 1x12
FRONTGIR	N/A
BAKGIR	SRAM NX Eagle
BREMSER	Shimano BR-MT500, hydraulic, Shimano RT-56 rotors [F]180mm, [R]160mm
BREMSEHENDLER	Shimano MT-501
KASSETT	SRAM NX Eagle, 11x50
KJEDE	SRAM NX Eagle
KRANK	TruVativ Descendent 6k, Eagle, 32t S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit
HJUL	
FELG	Giant XCR 2 Carbon 29 WheelSystem
NAV	Giant XCR 2 Carbon 29 WheelSystem
EIKE	Giant XCR 2 Carbon 29 WheelSystem
DEKK	Maxxis Recon Race 29x2.25, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.25" max tire size, 38t max chainring size

HØYDEPUNKTER

- Ramme: Advanced-Grade Composite, 12x148mm thru-axle
- Gaffel: RockShox SID SL, 100mm, 44mm offset, Boost 15x110mm Maxle Stealth, tapered steerer, remote lockout
- Girhendler: SRAM NX Eagle, 1x12
- Krank: TruVativ Descendent 6k, Eagle, 32t S:170mm, M:175mm, L:175mm, XL:175mm
- Farge: Knight Shield / Carbon

GEOMETRI

RAMME	S	M	L	XL
Seat Tube Length (mm)	380	431	475	525
Seat Tube Angle	73,5°	73,5°	73,5°	73,5°
Top Tube Length (mm)	595	614	635	665
Head Tube Length (mm)	95	95	105	115
Head Tube Angle	69,5°	69,5°	70,0°	70,0°
Fork Rake (mm)	43	43	43	43
Trail (mm)	94,9	94,9	94,9	94,9
Wheelbase (mm)	1087	1106	1128	1159
Chain Stay Length (mm)	425	425	425	425
Bottom Bracket Drop (mm)	58	58	58	58
Stack (mm)	604	604	613	632
Reach (mm)	416	435	453	477
Stand Over Height (mm)	737	764	791	829
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	70	80	90
Crank Length (mm)	170	175	175	175
Wheel Size	29"	29"	29"	29"

Alle spesifikasjonene kan endres uten varsel.